


DECT dongle **SDW D1 USB** | Headset **SDW 10 HS** | **SDW 30 HS** | **SDW 60 HS**

Specifications | Technische Daten | Caractéristiques techniques | Specifiche |
Especificaciones técnicas | Especificações | Technische specificaties | Προδιαγραφές |
Specifikationen | Specifikationer | Tekniset tiedot | Specyfikacje | Özellikler

DECT dongle **SDW D1 USB**



Dimensions (W x H x D)	20.5 x 23 x 8.5 mm / 0.81 x 0.91 x 0.33 in
Weight	5 g / 0.18 oz
DECT frequency range	1880 – 1900 MHz
RF Output Power	max. 100 mW (EIRP)
Temperature range	Operation: +5 °C to +45 °C / +41 °F to +113 °F Storage: -20 °C to +70 °C / -4 °F to +158 °F
Relative humidity	Operation: 20 to 85% Storage: 20 to 95%

In compliance with:

SDW D1 USB

Europe



Australia/New Zealand




Specifications | Technische Daten | Caractéristiques techniques | Specifiche |
Especificaciones técnicas | Especificações | Technische specificaties | Προδιαγραφές |
Specifikationer | Specifikationer | Tekniset tiedot | Specyfikacje | Özellikler

Headset

SDW 10 HS

model: SCDH1



Dimensions (W x H x D)	50 x 25 x 140 mm / 1.97 x 0.98 x 5.51 in
Weight with...	Ear hook: 44 g / 1.55 oz Headband: 58 g / 2.05 oz Neckband: 43 g / 1.52 oz
Talk time	Narrowband: up to 10 hours Wideband: up to 8 hours
Standby time	48 hours
Charging time with USB cable	50%: approx. 2 hours 100%: approx. 4 hours
Range (environment dependent)	Free line of sight: up to 135 m in office buildings: up to 40 m
Rechargeable battery (built-in)	Lithium Polymer; 3.7 V; 335 mAh
Frequency response speaker	100 Hz - 7.5 kHz
Microphone type	2 digital MEMS microphones, noise cancelling
DECT frequency range	EU: 1880 - 1900 MHz
RF output power	EU: max. 250 mW (EIRP)

Headset

SDW 30 HS

model: SCDH3

SDW 60 HS

model: SCDH2



Dimensions (W x H x D)	SDW 30 HS: 165 x 165 x 62 mm / 6.50 x 6.50 x 2.44 in SDW 60 HS: 165 x 170 x 62 mm / 6.50 x 6.69 x 2.44 in
Weight	SDW 30 HS: 100 g / 3.52 oz SDW 60 HS: 136 g / 4.80 oz
Talk time	Narrowband: up to 14 hours Wideband: up to 11 hours
Listening time	Wideband: up to 12 hours
Standby time	44 hours
Charging time with USB cable	50%: approx. 3 hours 100%: approx. 7 hours
Range (environment dependent)	Free line of sight: up to 135 m in office buildings: up to 40 m
Rechargeable battery (built-in)	Lithium Polymer; 3.7 V; 530 mAh
Frequency response speaker	50 Hz - 7.5 kHz
Microphone type	2 digital MEMS microphones, noise cancelling

In compliance with:

SDW 10 HS (model: SCDH1) | SDW 30 HS (model: SCDH3) | SDW 60 HS (model: SCDH2)

Europe



Australia/New Zealand



Sennheiser Communications A/S

Industriparken 27, DK-2750 Ballerup, Denmark, www.eposaudio.com, Printed in China, 08/20, 770-00296/A01